13

SUBJECT: Purchasing of an International MV607 w/ Grapple Loader

BID #: SC-0419-22 **OPEN DATE: 8/17/2022**

GENERAL GOVERNMENT AWARDS COMMITTEE

KIND AND BASIS OF CONTRACT: Service Contract - Date of award through September 30, 2023 with two (2) one (1) year renewal options

AGENCY: Fleet Management

BASIS OF AWARD: ALL OR NONE TO THE LOWEST RESPONSIVE, RESPONSIBLE BIDDER(S)

NUMBER OF BIDS INVITED: (11) **NUMBER RECEIVED:** (2) **OTHER:** (0)

SUMMARY OF BIDS AND RECOMMENDED ACTIONS:
Recommend approval of award to Cumberland International Trucks of Florida, LLC as the lowest responsive, responsible bidder. Period of service is one year from date of award, with two (2) one (1) year renewal options. Estimated initial expenditure amount not-to-exceed $169,690.00.

Funding Source: 51103.114001.564010.000000.00000500.00000.000000 – To be encumbered by purchase order

Attachments: Recommendation Memo, Bid Tabulation, Terms & Conditions, Specifications

ANALYST: _____ **RESPECTFULLY SUBMITTED** _____
Corey Sidlo GREGORY PEASE, CHIEF
PROCUREMENT DIVISION

CONCURRENCE BY: Crisencio Tongol, Chief, Fleet Management Division

(ALL AWARD ACTIONS SUBJECT TO LAWFULLY APPROPRIATED FUNDS)
ACTION OF GGAC COMMITTEE ON RECOMMENDATIONS ABOVE

MEMBERS APPROVING _____ MEMBERS DISAPPROVING _____ DATE: _____

_____ _____ OTHER: _____

_____ _____

_____ _____

ACTION OF AWARDING AUTHORITY DATE _____

APPROVED _____ DISAPPROVED _____

OTHER _____

SIGNATURE OF AUTHENTICATION _____

FINANCE AND ADMINSTRATION DEPARTMENT

FLEET MANAGEMENT DIVISION

Jacksonville

Where Florida Begins.

Date: August 23, 2022

To: Gregory Pease, Chief of Procurement Division

Thru: Cris Pongol, Chief of Fleet Management Division

From: David Hylazewski, Equipment Control Administrator DH

Re: Request Approval to of Award for SC-0419-22 Purchase of International MV607 w/Grapple Loader

---

Fleet Management Division is requesting approval of award to the lowest responsive, responsible bidder, Cumberland International Trucks of Florida, LLC. Period of Service is one year from date of award, with two (2) one (1) year renewal options. Total revised estimated expenditure not to exceed $169,690.00.

Funding Source: 51103.114001.564010.000000.00000500.00000.000000
to be encumbered by purchase order

TITLE: PURCHASE OF INTERNATIONAL MV607 W GRAPPLE LOADER BODY

BID NO.: SC-0419-22

OPEN DATE: AUGUST 17, 2022 @ 2 P.M.

ANALYST: JACLYN STAMOS

No. Invited: (11) No. Received (2) No Bids: (0)

Recorded By: MELISSA PIERCE Announcer: PEARL MITCHELL

ITEM	DESCRIPTION	EST. QTY	UNIT	Cumberland International Trucks of Florida, LLC		Ring Power Corporation			
				UNIT PRICE	EXTENDED TOTAL	UNIT PRICE	EXTENDED TOTAL	UNIT PRICE	EXTENDED TOTAL
1	INTERNATIONAL MV607 W GRAPPLE LOADER BODY OR EQUIVALENT	1	EA	$ 169,690.00	$ 169,690.00	$ 196,848.00	$ 196,848.00		$ -
			GRAND TOTAL	$ 169,690.00		$ 196,848.00		$ -	
			DELIVERY TERMS	270 BUSINESS DAYS		NONE STATED			
			CONFLICT OF INTEREST:	Y		Y			
			BUY AMERICAN ACT	Y		N			
			ADDENDUM(0):						
			NOTES	2024 INTERNATIONAL MV607 W GRAPPLE LOADER BODY		2022 PALFINGER M100L72 HYDRAULTIC LOADER (SPECS PROVIDED) HV607 SBA			

TERMS AND CONDITIONS

SCOPE

The Fleet Management Division of the City of Jacksonville, Florida is currently accepting bids to obtain source(s) of supply for the items as outlined in the bid documents provided. The purpose of this bid invitation is to obtain information about your firm and its ability to provide these items and to obtain pricing commitments for Purchase of 2023 International MV607 w/Grapple Loader Body or Equivalent as listed in the bid documents.

AWARD

Award will be ALL OR NONE to the lowest responsive, responsible bidder. ALL awards are subject to the availability of funds.

TERM OF AGREEMENT

The term of this agreement is One year from date of award, with two (2) one (1) year renewal options. Renewal Options may be exercised at the discretion of the City based on supplier performance and adherence to the terms and condition set forth in the bid documents.

- As per Section 126.114 of the City of Jacksonville Ordinance Code, preference will be given to a responsive and responsible vendor offering American manufactured, assembled, or produced goods, and who is within 5% of the lowest responsive and responsible bidder. To receive this preference, the bidder must complete the attached Buy American Preference Compliance Certificate and attach supporting documentation and/or evidence attesting that at least 51% offered in the bid response is manufactured, assembled or produced in the United States.
    - Bidder is not required to submit for the Buy American Preference. Bidders may quote items less than 51% American made but will not be eligible for the preference.
    - Restrictions and exemptions may apply. Please refer to Section 126.114 for specifics.

COMPLIANCE WITH SPECIFICATIONS

The bidder, by affixing their signature to the bid form submitted, agrees to provide item(s)/service(s) in accordance with the bid documents provided. Bid only a single offering for each bid item. Multiple offerings, alternates (unless stated) and or stipulations may be cause for bid rejection. Bid only on forms provided herein unless otherwise stated. Bid submissions shall be in ink or typewritten. All corrections must be initialed.

STATE CONTRACTS

The City reserves the right to utilize contracts established by the State of Florida and or other governmental agencies for item(s)/service(s) covered under this bid. The city reserves the right to cancel this contract in whole or in part for such item(s)/service(s).

QUANTITIES

Quantities indicated reflect the estimated quantities to be purchased throughout the contract period and are subject to fluctuation in accordance with actual requirements and budgetary constraints. The City reserves the right to purchase more than the estimated quantities listed or not to make any purchase against this bid if it so deems necessary anytime during the contract period.

TERMS AND CONDITIONS

The City of Jacksonville reserves the right to add or delete options as necessary during the contract period.

ESCALATION/DE-ESCALATION

All pricing submitted shall remain firm for the initial term period. Upon renewal (if applicable), a supplier may submit in writing a request for price escalation/de-escalation for the percentage of change as listed in the Consumer Pricing Index (CPI) and/or documentation notifying of an industry wide increase. The City reserves the right to decline any price increase request.

PRICES

All unit prices shall include freight, delivery, and handling charges to the delivery location as outlined in the bid documents.

DELIVERY

Delivered to: 2581 Commonwealth Avenue, Jacksonville, Florida 32254 between the hours of 7:00 am and 2:30 pm, Monday thru Friday. There will be no exceptions to the times stated unless prior arrangement with Fleet Management has been made. No acceptance of any vehicles will take place during any City observed holiday. All orders are FOB destination.

A packing list shall accompany all shipments, which shall indicate, at a minimum, the following: purchase order number, item number and description, date of shipment, quantity ordered and shipped, unit prices, and unit of measure.

PICK UP AND RETURNS

COJ will have 48 hours to inspect all vehicles delivered. COJ will use the same form the vendor is required to use. Any vehicles with discrepancies will be picked up within 24 hours and returned immediately or the vendor can send a technician to COJ Fleet Management to correct the discrepancy within 24 hours. The vendor will repair and return any vehicles picked up at Fleet before delivery of additional vehicles. This return and repair will not relieve the vendor of their monthly requirements.

SUPPLIER ACCESSIBILITY

The City or its representative must be able to contact, during normal business hours, by telephone or email any supplier providing goods or services to the city or its agencies. Any supplier accessibility requirements outlined in the specifications supersede this section.

The City may request, during the term of this bid, reports including but not limited to; usage, pricing, and delivery. Suppliers will be required to provide reports requested in hard copy and electronic format as required.

INVOICING

Invoices will be issued once supplies/services are delivered and/or rendered to the City of Jacksonville or its agencies. At a minimum, invoices must include purchase order number, item number and description, date of shipment, quantity ordered and shipped, unit prices, unit of measure, and extended totals. Payment terms are Net 30 days. All original invoices shall be submitted to: Fleet Management Division, 2581 Commonwealth Avenue, Jacksonville, Florida 32254.

INSURANCE/INDEMNIFICATION

Each supplier shall maintain, for the entire term of this bid, current insurance coverage as stated in the bid documents. All insurance certificates shall list the City of Jacksonville as an additional insured. The awarded vendor will be required to submit the copy of insurance certificate within ten (10) days from date of receipt of award notice. Bid number should be listed on certificate.

SPECIFICATIONS
2023 INTERNATIONAL MV607 WITH GRAPPLE LOADER BODY (OR EQUIVALENT)

A. 20230MV607 SBA (MV607) - MODEL

1. BASE CHASSIS, Model MV607 SBA with 278.00 Wheelbase, 210.90 CA, and 73.00 Axle to Frame.
2. TOW HOOK, FRONT - (2) Frame Mounted
3. AXLE CONFIGURATION {Navistar} - 4x2
4. FRAME RAILS - Heat Treated Alloy Steel (120,000 PSI Yield); 10.375" x 3.705" x 0.438" (263.5mm x 94.1mm x 11.1mm); 456.0" (11582mm) Maximum OAL, Limited to 33,000 lb Maximum GVWR
5. BUMPER, FRONT - Full Width, Aerodynamic, Steel; 0.142" Material Thickness
6. WHEELBASE RANGE 256" (650cm) Through and Including 311" (790cm)
7. AXLE, FRONT NON-DRIVING {Navistar Select} I-Beam Type, 12,000-lb Capacity8.
8. SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 12,000-lb Capacity; with Shock Absorbers
9. BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
10. DRAIN VALVE {Berg} with Pull Chain, for Air Tank
11. AIR BRAKE ABS {Bendix Antilock Brake System} Full Vehicle Wheel Control System (4-Channel)
12. AIR DRYER {Bendix AD-IP} with Heater
13. BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn
14. BRAKE CHAMBERS, REAR AXLE {Bendix Ever Sure} 30/30 Spring Brake
15. BRAKES, FRONT, AIR CAM S-Cam; 15.0" x 4.0"; Includes 20 Sq. In. Long Stroke Brake Chambers
16. BRAKES, REAR AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake
17. AIR COMPRESSOR {Cummins} 18.7 CFM Capacity
18. AIR DRYER LOCATION Mounted Outside Right Rail, Forward of Front Wheel
19. AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Right Rail, Under Cab
20. STEERING COLUMN Tilting
21. STEERING WHEEL 4-Spoke; 18" Dia., Black
22. STEERING GEAR {Sheppard M100} Power
23. EXHAUST SYSTEM Single, Horizontal After treatment Device, Frame Mounted Under Right Rail, Back of Cab, Includes Short Horizontal Tail Pipe
24. ELECTRICAL SYSTEM 12-Volt, Standard Equipment
25. CIGAR LIGHTER Includes Ash Cup
26. HORN, ELECTRIC (2) Disc Style
27. POWER SOURCE Cigar Type Receptacle without Plug and Cord
28. ALTERNATOR {Leece-Neville AVI160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, with Remote Sense
29. BODY BUILDER WIRING To Rear of Frame, with Stop, Tail, Turn, and Marker Lights Circuits, Ignition Controlled Auxiliary Feed and Ground, Less Trailer Socket
30. BATTERY SYSTEM {Fleetrite} Maintenance-Free, (2) 12-Volt 1900CCA Total
31. RADIO AM/FM/WB/Clock/3.5MM Auxiliary Input
32. SPEAKERS (2) 5.25" Dual Cone Mounted in Both B-Pillars
33. BACK-UP ALARM Electric, 102 dBA
34. BATTERY BOX Steel, with Plastic Cover, 25" Wide, 2 or 3 Battery Capacity, Mounted Right Side Under Cab
35. WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time
36. HEADLIGHTS - Halogen; Composite Aero Design for Two Light System; Includes Daytime Running Lights TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on
37. STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection
38. INDICATOR, LOW COOLANT LEVEL with Audible Alarm
39. ALARM, PARKING BRAKE - Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, with Ignition "OFF" and any Door Opened
40. CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses
41. HORN, AIR, Black, Single Trumpet, with Lanyard Pull Cord
42. LOGOS EXTERIOR Model Badges
43. LOGOS EXTERIOR, ENGINE Badges
44. GRILLE Chrome
45. FRONT END Tilting, Fiberglass, with Three Piece Construction
46. PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes: PAINT SCHEMATIC ID LETTERS "WP", PAINT TYPE Base Coat/Clear Coat, 1-2 Ton, PROMOTIONAL PACKAGE Government Silver Package

47. MUD FLAPS, FRONT WHEELS (2) Rubber, Behind Front Wheels, Mounted on Fender Extension
48. CLUTCH Omit Item (Clutch & Control)
49. ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
50. ENGINE, DIESEL {Cummins B6.7 200} EPA 2017, 200HP @ 2400 RPM, 520 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 200 Peak HP (Max)
51. VENDOR WARRANTY, ENGINE {Cummins} B6.7 Engine, 3-Year Unlimited Miles Standard Warranty
52. FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed with Residual Torque Device for Disengaged Fan Speed
53. RADIATOR Aluminum; 2-Row, Cross Flow, Over Under System, 717 SqIn Louvered, with 313 SqIn Charge Air Cooler. with In-Tank Transmission Cooler
54. AIR CLEANER with Service Protection Element
55. FEDERAL EMISSIONS {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2018
56. THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic, Mobile, Variable Speed; (Range 2 to 20 MPH) Mounted on Steering Wheel
57. OIL Pan
58. EMISSION COMPLIANCE Federal, Does not Comply with California Clean air idle regulations
59. ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; with Ignition Switch. Control for Cummins ISB/B6.7 or ISL/L9 Engines
60. TRANSMISSION, AUTOMATIC {Allison 3500 RDS} 5th Generation Controls, Wide Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway
61. TRANSMISSION SHIFT CONTROL for Column Mounted Stalk Shifter
62. TRANSMISSION OIL Synthetic; 29 thru 42 Pints
63. ALLISON SPARE INPUT/OUTPUT - for Rugged Duty Series (RDS); General Purpose Trucks, Construction
64. SHIFT CONTROL PARAMETERS Allison 3000 or 4000 Series Transmissions, 5th Generation Controls, Performance Programming
65. PTO LOCATION Left Side of Transmission
66. AXLE, REAR, SINGLE {Navistar Select} Single Reduction, 23,000-lb Capacity, R Wheel Ends. Gear Ratio: 4.30
67. SUSPENSION, RR, SPRING, SINGLE Vari-Rate; 23,500-lb Capacity, with 4500 lb Auxiliary Rubber Spring
68. FUEL/WATER SEPARATOR 12 VDC Electric Heater, Includes Pre-Heater, Includes Water-in-Fuel Sensor, Cummins Supplied on Engine
69. FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 50 US Gal (189L), with Quick Connect Outlet, Mounted Left Side, Under Cab
70. DEF TANK U.S. Gal. 26.5L Capacity, Frame Mounted Outside Left Rail, Under Cab
71. CAB Conventional
72. AIR CONDITIONER w/Integral Heater & Defroster
73. GAUGE CLUSTER Base Level: English w/English Speedometer and Tachometer, for air brake chassis, included engine coolant temperature, primary and secondary air pressure, fuel and DEF gauges, oil pressure gauge, included 3-inch Monochromatic text Display.
74. GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission
75. IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
76. SEAT, DRIVER {National 2000} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, with 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust
77. GRAB HANDLE (2) Black, Aluminum; for Cab Entry Mounted Left and Right each Side at "B" Pillar
78. SEAT, TWO-MAN PASSENGER {National} Fixed Back, Integrated Headrest in Both Occupant Positions, Vinyl, with Under Seat Storage Compartment
79. MIRRORS (2) Thermostatically Controlled Heated Heads, Black Heads, Brackets and Arms, 7.55" x 14.1" Flat Glass, 7.48" x 6.77" Convex Glass Both Sides
80. CAB INTERIOR TRIM - CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger. DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center. SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap.
81. CAB REAR SUSPENSION Air Suspension, for Mid Cab Height.
82. FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood.
83. WINDOW, MANUAL (2) and Manual Door Locks, Left and Right Doors.
84. INSTRUMENT PANEL Flat Panel
85. ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per door, for use with Regular and Extended Cabs

86. WHEELS, FRONT (Accuride 29001) DISC; 22.5x7.50 Rims, Powder coat steel, 5-Hand hole, 10-Stud, 285.75mm BC, hub-piloted, flanged nut with Steel Hubs
87. WHEELS REAR (Accuride 29001) DUAL Disc; 22.5x87.50 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut w/Steel Hubs. Two (2) Tires, FRONT 12R22.5 Load Range G HSR2 Continental), 498 rev/mile, 75 MPH, All-Position, Two (2) Tires, REAR 12R22.5 Load Range G HSR2 (Continental), 498 rev/mile, 75 MPH All Position

B. SERVICES SECTION:

WARRANTY Standard for MV Series, Effective with Vehicles Built July 1, 2017, or Later, CTS-2020A. SERVICES, TOWING {Navistar} Service Call to 36-Month/Unlimited Mileage to the Nearest Navistar Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; $275 (USA) Maximum Benefit per Incident. SRV CONTRACT, EXT CMMS ENGINE {Cummins} To 60-Month/150,000 Miles (240,000 km), Extended Cummins B6.7 Engine Coverage, Protection Plan 1, (Truck Application Only)

C. DEALER INSTALLED OPTION:

1. **Minimum Chassis Requirements:**
   a. 33,000 GVW
   b. 210" Clear CA Minimum
   c. 72" AF Minimum
   d. Fuel tanks must not protrude beyond the back of the cab
   e. Battery box underneath cab, or back 62" on the RH side, and 90" on the LH side from clear back of cab (BOC), toward the rear axle
   f. Air tanks underneath the cab, or tucked inside the frame rails out of the way
   g. Horizontal exhaust extended to mid-body
   h. Exterior cab grab handles (both sides)
2. **Chassis Specifications:**
   a. Heavy Duty 30" Diameter Slewing Ring Bearing
   b. 2 Stage Planetary Gear Drive
   c. Hot Shift PTO
   d. Direct Mount Pump
   e. 4-Way Adjustable Stabilizers
   f. Stabilizer LED Strobe Lights
   g. Dual Operator Control Stations: Controls Forward & Level Platform
   h. 24" Walk-Thru
   i. Main Boom, Tip Boom and Tip Boom Extension
   j. Hose Retract Box
   k. Municipal 48" x 60" Bucket: Bolt-On, Reversible Bucket Edges; Bucket Cylinder Covers
   l. 360 Degree Continuous Rotation
   m. 20' Tapered Dump Body (42"-74")
   n. 3/16" Single Sheet Floor
   o. 4" Crossmembers on 12" Centers
   p. 10GA Sides
   q. 10GA Side Posts on 24" Centers
   r. 1/4" Rear Posts
   s. Single Rear Door
   t. Dual Upper Rear Door/Tailgate Amber Strobe Lights
   u. 23 Ton Scissor Hoist, Single Body Prop
   v. Primed and Painted Solid Color
   w. Undercoating on Bottom of Dump Body